

IN THE CLAIMS

Claims 1, 3-5 and 8-16 are pending in this application. Please cancel claims 2 and 6-7 without prejudice or disclaimer, and amend claims 1, 3-5, 8-9 and 13-15 as follows:

1. (Currently Amended) A display control device comprising:
 - an image data generating unit for generating image data for a plurality of display faces ~~for each of the display faces~~ according to a series of data command, each of the plurality of display faces having a plurality of image data;
 - an image data storage unit for storing generated image data respectively in storage areas of a memory unit, the storage areas corresponding to the display faces; and
 - a display processing ~~circuit~~ unit for reading image data of a plurality of display faces stored in the memory unit to superimpose the image data, ~~[[and]]~~ converting the image data into display output signals, and setting a display switching information,
wherein the display switching information indicates whether or not the storage area from which the image data is read is switched,
 - wherein the display processing unit is operable to switch the storage areas from which ~~the image data is read are capable of switching for each display face by the display processing circuit~~ according to the display switching information, in response to the display control device receiving a display vertical synchronous signal of a display device.
2. (Canceled)
3. (Currently Amended) The display control device according to claim 1, further comprising a first instruction,
 - wherein the first instruction indicating ~~[[the]]~~ termination of generation of image data for one display face includes a plurality of display switching enable bits indicating the display switching information ~~whether or not a storage area from which image data is read is switched~~ for each of the plurality of display faces, and
 - wherein ~~the setting of switching to a~~ the display processing unit is operable to switch ~~the storage area from which the image data is read is performed based on~~ according to the display switching enable bits.

4. (Currently Amended) The display control device according to claim 1, further comprising a first register for storing information indicating ~~from which storage area the image data of each display face is read~~ the display switching information,
wherein the display processing unit is operable to switch the storage areas according to the information of the first register.
~~wherein the setting of switching to a storage area from which the image data is read is performed by updating the first register.~~
5. (Currently Amended) The display control device according to claim 4, further comprising an address register for storing the addresses of a plurality of storage areas in which the image data of each display face is stored,
wherein the display processing ~~circuit~~ unit reads image data, ~~using~~ indicated by an address selected from the address register based on information of the first register ~~from the address register~~.
- 6-7. (Canceled)
8. (Currently Amended) The display control device according to claim ~~[[7]]~~3,
wherein information ~~stored in~~ of the first register is ~~updated by information contained in~~ set according to the display switching enable bits.
9. (Currently Amended) A microcomputer comprising:
a central processing unit;
a display control device for performing drawing processing and display control; and
a memory,
wherein the display control device includes a display unit that controls display information indicating storage destinations of image data to output display signals to a display device connected to the outside,
wherein the display unit includes a plurality of display plane processing units each using image data of a plurality of display faces that is capable of being displayed in a superimposed form on a display screen of the display device,

wherein the display plane processing units include a plurality of pieces of display information indicating the storage destinations of image data of corresponding display faces, [[and]]

wherein the display control device is capable of updating the display information used in the plural display plane processing units after receiving a first instruction indicating the termination of drawing processing, and

wherein the display unit is operable to switch the storage destinations of image data of display faces in response to the display control device receiving a display vertical signal of the display device.

10. (Original) The microcomputer according to claim 9,
wherein the display information used in the plural display plane processing units is updated at timing synchronous with the display transition synchronous signal of the display device.
11. (Original) The microcomputer according to claim 9,
wherein the first instruction includes information for updating the display information.
12. (Original) The microcomputer according to claim 9,
wherein the display information is address information of storage unit in which image data is stored.
13. (Currently Amended) The microcomputer according to claim [[10]] 9,
wherein two or more pieces of the display information used in the display plane processing units is capable of being updated at the same time in response to the first instruction being executed by the display control device.

14. (Currently Amended) A navigation system comprising:
the display control device comprising:
an image data generating unit for generating image data for a plurality of display faces for each of the display faces according to a series of data commands;
an image data storage unit for storing generated image data respectively in storage areas of memory unit, the storage areas corresponding to the display faces; and
a display processing circuit for reading image data of a plurality of display faces stored in the memory unit to superimpose the image data, and converting the image data into display output signals, and setting a display switching information,
wherein the storage areas from which image data is read are capable of switching for each display face by the display processing circuit;
a central processing unit for generating the series of commands executed by the display control device or data;
a memory unit for storing image data generated by the display control device;
a display device; and
a memory device for storing map information,
wherein image data is generated by the display control device according to the map information read from the memory device and a map is displayed on the display device,
wherein the display switching information indicates whether or not the storage area from which the image data is read is switched, and
wherein the display processing circuit is operable to switch the storage areas from which image data is read according to the display switching information in response to the display control device receiving a display vertical synchronous signal of a display device.
15. (Currently Amended) A display control device comprising:
an image data generating unit for generating image data of a plurality of display faces according to a series of commands ~~or data~~;
an image data storage unit for storing generated image data respectively in storage areas of memory unit, the storage areas corresponding to the display faces; and
a display processing circuit for reading image data of a plurality of display faces stored in the memory unit to superimpose the image data, and converting the image data into display output signals,
wherein the image data of the plural display faces is comprised of image data further

subjected to superimposing processing for each display face and a plurality of image data preceding and following the image data , and
wherein the storage area of image data of the display faces is operable to switch
according to switch information from the image data processing unit in response to the
display control device receiving a display vertical synchronous signal.

16. (Original) The display control device according to claim 15,
wherein setting is made whether or not a storage area from which the image data is read is switched for each display face at the termination of generation of image data for one display face.